



MACHINE TOOLS

Since 1995



Hydraulic Press Brake



TECHNICAL SPECIFICATION

MODEL	Tonage	Table Length	Bending Dimensions in MS, UTS 45 Kg / mm2	Table Width	Clear Pass	Ram Stroke	Open Height	Throat Depth	Approach Pressing Return	Power	Packing Dimensions in mm (L x W x H)
		mm	mm	mm	mm	mm	mm	mm	Speed	H.P.	
APBR-212	20	1270	1270X2.5	150	1000	100	250	100	35-9-35	2	1500
APBR-215	20	1525	1525X2	150	1050	100	250	100	35-9-35	2	1700x1050x1900
APBR-312	30	1270	1270X3	150	1000	100	250	100	35-9-35	2	1500
APBR-315	30	1525	1525X2.5	150	1050	100	250	100	35-9-35	2	1700
APBR-320	30	2030	2030X2	150	1550	100	250	200	30-7-30	3	2200x1150x1900
APBR-325	30	2540	2540X1.6	150	2050	100	250	200	30-7-30	3	2700
APBR-412	40	1270	1270X4	150	1000	100	250	200	30-7-30	3	1500
APBR-415	40	1525	1525X3	150	1050	100	250	200	30-7-30	3	1700
APBR-420	40	2030	2030X2.5	150	1550	100	250	200	30-7-30	3	2200
APBR-425	40	2540	2540X2	150	2050	100	250	200	40-8-40	3	2700x1150x1900
APBR-515	50	1525	1525X4	150	1050	100	250	200	40-8-40	3	1700
APBR-520	50	2030	2030X3	150	1550	100	250	200	40-8-40	3	2200
APBR-525	50	2540	2540X2.5	190	2050	100	250	200	35-7-35	5	2700x1050x1900
APBR-612	60	1270	1270X6	190	1000	150	250	200	35-7-35	5	1500
APBR-615	60	1525	1525X5	190	1050	150	250	200	35-7-35	5	1700
APBR-620	60	2030	2030X4	190	1550	150	250	200	35-7-35	5	2200
APBR-625	60	2540	2540X3	190	2050	150	330	200	30-5-30	5	2700x1200x2000
APBR-630	60	3125	3125X2	190	2550	150	330	200	30-5-30	5	3350
APBR-812	80	1270	1270X8	190	1000	150	330	200	30-5-30	5	1500
APBR-815	80	1525	1525X6	190	1050	150	330	200	30-5-30	5	1700
APBR-820	80	2030	2030X5	190	1550	150	330	200	30-5-30	5	2200
APBR-825	80	2540	2540X4	190	2050	150	330	200	38-6-45	7.5	2700x1550x2300
APBR-830	80	3125	3125X3	190	2550	150	330	200	38-6-45	7.5	3350x1550x2300
APBR-1015	100	1525	1525X8	190	1050	150	330	200	38-6-45	7.5	1700
APBR-1020	100	2030	2030X6	190	1550	150	330	200	38-6-45	7.5	2200
APBR-1025	100	2540	2540X5	190	2050	150	330	200	38-6-45	7.5	2700x1550x2300
APBR-1030	100	3125	3125X4	190	2550	150	330	200	38-6-45	7.5	3350x1550x2300
APBR-1040	100	4000	4000X3	190	3250	150	330	200	38-6-45	7.5	4250x1650x2300
APBR-1215	120	1525	1525X10	230	1050	150	330	300	38-6-45	7.5	1700
APBR-1220	120	2030	2030X8	230	1550	150	330	300	38-6-45	7.5	2200
APBR-1225	120	2540	2540X6	230	2050	150	350	300	38-5-40	10	2750x1650x2500
APBR-1230	120	3125	3125X5	230	2550	150	350	300	38-5-40	10	3350x1650x2500
APBR-1240	120	4000	4000X4	230	3250	150	350	300	38-5-40	10	4250x1650x2500
APBR-1615	160	1525	1525X12	230	1050	150	350	300	38-5-40	10	1700
APBR-1620	160	2030	2030X10	230	1550	150	350	300	38-5-40	10	2200
APBR-1625	160	2540	2540X8	230	2050	150	350	300	35-6-40	15	2750x1800x2600
APBR-1630	160	3125	3125X6	230	2550	150	350	300	35-6-40	15	3350x1800x2600
APBR-1640	160	4000	4000X5	300	3250	150	350	300	35-6-40	15	4250
APBR-2020	200	2030	2030X12	250	1550	200	350	300	35-6-40	15	2200
APBR-2025	200	2540	2540X10	250	2050	200	400	300	35-7-35	20	2850x2050x2750
APBR-2030	200	3125	3125X8	250	2550	200	400	300	35-7-35	20	3350x2050x2750
APBR-2040	200	4000	4000X6	300	3250	200	400	300	35-7-35	20	
APBR-2520	250	2030	2030X14	250	1550	200	400	300	35-7-35	20	
APBR-2525	250	2540	2540X12	250	2050	200	400	300	35-7-35	20	
APBR-2530	250	3125	3125X10	300	2550	200	400	300	35-7-35	20	
APBR-2540	250	4000	4000X8	300	3250	200	400	300	35-7-35	20	
APBR-3025	300	2540	2540X15	300	2050	200	400	300	35-7-35	20	
APBR-3030	300	3125	3125X12	300	2550	200	400	300	30-6-35	30	3350x2150x2900
APBR-3040	300	4000	4000X10	300	3250	200	400	300	30-6-35	30	
APBR-3050	300	5000	5000X8	300		200	400	300	30-6-35	30	
APBR-3060	300	6000	6000X6	300		200	400	300	30-6-35	30	