



MACHINE TOOLS

Since 1995



Hydraulic Shearing



## TECHNICAL SPECIFICATION

MODEL	Cutting Length	Shearing Capacity				Nominal Rake Angle	Rake Angle Range	Max. Front Gauge	Max. Back Gauge	Stroke / Minute		No. of Holddowns	Holding Force Kgs.	Power H.P.	Over all Dimensions			Approx. Weight Kgs.
		M.S.	S.S.	Nomi. Rake	Maxi. Rake					Mini. Rack Angle	Maxi. Rack Angle				Length	Weight	Height	
AHVR-315	1525	3	4	2	3	1.5°	1-2.5°	1234	123	20	11	8	1700	3	2150	1650	1850	2700
AHVR-325	2540	3	4			1.5°	1-2.5°			25	13	13	2300	5	3200	1850	1950	3500
AHVR-415	1525	4	6			1.6°	1-3°			25	13	8	4500	7.5	2250	1850	2050	3200
AHVR-425	2540	4	6			1.6°	1-3°			21	8	13	8000	7.5	3300	2250	2400	5000
AHVR-440	4000	4	6			1.6°	1-3°			20	6	20	12000	10	4500	2250	2400	8100
AHVR-620	2030	6	8			1.75°	1-3°			20	7	11	6500	10	2750	1900	2100	4300
AHVR-630	3125	6	8			1.75°	1-3°			22	6	16	10800	15	3800	2250	2500	7200
AHVR-815	1525	8	10			2°	1-3°			15	8	8	10500	10	2250	2050	2200	4500
AHVR-825	2540	8	10			2°	1-3°			20	8	13	16500	20	3300	2350	2600	7500
AHVR-840	4000	8	10			2°	1-3°			18	8	20	23000	30	4800	2350	2600	12500
AHVR-1020	2030	10	13			2°	1-3°			18	8	11	13000	15	2750	2050	2300	6000
AHVR-1030	3125	10	13			2°	1-3°			12	6	16	20000	20	3800	2500	2800	11500
AHVR-1325	2540	13	16			2°	1-3°			13	6	13	20000	25	3350	2600	2800	8000
AHVR-1340	4000	13	16			2°	1-3°			9	4	20	25000	30	4850	2600	2800	15500
AHVR-1630	3125	16	-			2.5°	1-3°			12	5	16	28000	30	4000	2600	2900	17000
AHVR-2025	2540	20	-			2.5°	1-3°			12	5	13	28000	40	3500	2750	3000	18000
AHVR-2040	4000	20	-			2.5°	1-3°			9	4	20	40000	50	5100	2800	3000	24000
AHVR-2530	3125	25	-			2.5°	1-3°			8	4	16	45000	60	4000	2900	3200	28000
AHVR-2540	4000	25	-			2.5°	1-3°			7	4	20	50000	70	5100	2900	3200	32000

- \* POWER SUPPLY ; 400/440 VOLTS, 3 PHASE, 50 CYCLES.
- \* AS DAY IMPROVEMENTS ARE CONTEMPLATED FOR BETTER PERFORMANCE OF THE MACHINE.
- \* WE RESERVE THE RIGHTS TO ALTER THE SPECIFICATIONS WITHOUT PRIOR NOTICE.
- \* ALL DIMENSIONS ARE IN MM.