



MACHINE TOOLS

Since 1995



Under Crank Shering



TECHNICAL SPECIFICATION

MODEL	Cutting Capacity	Length Bet. Housing	Stroke / Minute	Height of Table	Weight of Table	Hold Down to Knife Edge	Rake Angle / Meter	Max. Front Gauge	Max. Back Gauge	Knives Size			Main Motor H. P.	Over all Dimensions			Approx. Weight Kgs.
										Length	Thickness	Width		Length	Weight	Height	
AUS-16	685X1	985	65	775	250	10	40	600	600	685	12	50	2/1440	1700	1000	1000	650
AUS-110	1000X1	1300	65	775	250	10	36	600	600	1000	12	50	2/1440	1900	1000	1000	1000
AUS-112	1270X1	1600	65	775	300	10	28	600	600	1270	12	50	2/1440	2215	1200	1060	1300
AUS-115	1525X1	1950	60	775	350	10	28	600	600	1525	12	50	3/1440	2450	1200	1060	1500
AUS-120	2030X1	2350	55	775	375	10	24	600	600	2030	12	50	5/1440	2970	1200	1060	1700
AUS-125	2540X1	2810	55	800	375	10	20	600	600	2540	12	50	5/1440	3460	1200	1060	2100
AUS-26	685X2	985	65	800	300	15	40	600	600	685	12	50	2/1440	1700	1100	1100	1000
AUS-210	1000X2	1300	60	800	350	15	38	600	600	1000	14	50	2/1440	1900	1100	1100	1300
AUS-212	1270X2	1600	60	800	375	15	36	600	600	1270	14	50	3/1440	2215	1300	1160	1600
AUS-215	1525X2	1950	55	800	375	15	36	600	600	1525	14	50	3/1440	2450	1300	1160	1900
AUS-220	2030X2	2350	55	800	375	15	28	600	600	2030	14	63	5/1440	2970	1300	1160	2500
AUS-225	2540X2	2810	50	875	425	15	28	600	750	2540	14	63	5/1440	3460	1300	1160	3000
AUS-230	3125X2	3460	50	875	425	15	24	600	750	3125	14	63	7.5/1440	4110	1300	1160	3500
AUS-46	685X4	985	55	800	350	20	40	600	600	685	14	50	2/1440	1700	1300	1200	1500
AUS-410	1000X4	1300	55	800	375	20	38	600	600	1000	18	63	3/1440	1900	1300	1200	2100
AUS-412	1270X4	1600	55	800	425	20	38	600	600	1270	18	63	5/1440	2215	1500	1260	2500
AUS-415	1525X4	1950	50	875	425	20	36	600	600	1525	18	63	5/1440	2450	1500	1260	2650
AUS-420	2030X4	2350	50	875	425	20	28	600	600	2030	18	63	7.5/1440	2970	1500	1260	2900
AUS-425	2540X4	2810	45	875	425	20	28	600	750	2540	18	75	7.5/1440	3460	1500	1260	4000
AUS-430	3125X4	3460	45	875	425	20	24	600	750	3125	18	75	10/1440	4110	1500	1260	4550

• STANDARD ACCESSORIES

- ▶ Motor Pulley
- ▶ Fly wheel & Gear Guard
- ▶ Oil cups for lubrication point
- ▶ Foot Paddle
- ▶ Front Gauge
- ▶ Back Gauge (manual operated)
- ▶ Handle for back gauge

• OPTIONAL ACCESSORIES

- ▶ Lubrication pump manual
- ▶ Lubrication pump automatic
- ▶ Electrical & Accessories
- ▶ Stroke Counter
- ▶ Tie Rod
- ▶ Motorize Back Gauge
- ▶ Hydraulic Hold Down
- ▶ Pneumatic Clutch

- ★ POWER SUPPLY ; 400/440 VOLTS, 3 PHASE, 50 CYCLES.
- ★ AS DAY IMPROVEMENTS ARE CONTEMPLATED FOR BETTER PERFORMANCE OF THE MACHINE.
- ★ WE RESERVE THE RIGHTS TO ALTER THE SPECIFICATIONS WITHOUT PRIOR NOTICE.
- ★ ALL DIMENSIONS ARE IN MM.